

# Assemble Manual

## Model # 4002



Step 1: Check all the parts ready. Loose the screws and lock the suspension.



Step 2: Insert the wheel by push it into the axle.



Step 3. Pull out the Kick stand.



Step 4: Assemble the tow bar to the trailer frame by using the two knobs . Locked it by using gasket and butterfly knobs..Now your trailer is ready for use.



#### Step 5: Fitting the coupling

a: Secure the saddle-support mounting, with the help of the plastic shims, to the saddle pillar of your bicycle.

b: Now use the M8x50mm screw that is ready-fitted to the saddle support mounting to attach the ball-head coupling to the saddle support mounting as above image.

Now Your trailer is ready for use!

#### **Safety Instructions:**

- The trailer is intended to carry goods only. No human passengers!
- Maximum load: 100 kgs or 200 lbs
- Maximum speed: 16km/hour. or 10 mi/hr
- Always wear a helmet when riding.
- Carefully check the bolts, nuts and safety pins. Make sure that all these parts are properly tightened or locked.
- Be aware that riding with the trailer increases your braking distance and may affect your ability to control the bicycle. Thoroughly practice in a safe area until you become familiar with it.
- Only use factory-supplied wheels, with the tires inflated to 30-35 P.S.I. Check pressure before each use.
- Do not make any alterations to the trailer or hitch, which could result in injury or death.